

SPECIFICATIONS	
Weight capacity	Up to 136 kg (300 lbs.)
Maximum speed <sup>1</sup>	Up to 6.44 km/h (4 mph)
Ground clearance	3.81 cm (1.5") (at anti-tips and motors)
Turning radius <sup>2</sup>	61 cm (24")
Overall length <sup>2,6</sup>	87.3 cm (37.375") without front riggings
Overall width <sup>2</sup>	58.4 cm (23")
Drive wheels	22.86 cm (9") solid
Anti-tips	7.62 cm (3") solid, front-mounted
Casters	15.24 cm (6") solid, rear-mounted
Suspension	Limited
Drivetrain	Two-motor, in-line, front-wheel drive
Braking system	Intelligent braking (electronic, regenerative disc brakes)
Standard electronics	40 amp, PG GC 3 controller
Standard seat	Comfort high-back
Specialty controls	N/A
Battery charger	Off-board, 3 amp
Per-charge range <sup>1,4</sup>	Up to 21.97 km (13.65 miles)
Battery requirements	(2) 12 volt deep-cycle
Battery size (largest)	(U-1) 30-34 AH
Battery weight <sup>3</sup> Base weight Standard seat weight	11.11 kg (24.5 lbs.) each 51 kg (112.5 lbs.) 17.7 kg (39 lbs.) (Comfort high-back)
Max. seating dimensions	50.8 cm x 50.8 cm (20" x 20")
Warranty	2-year limited

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.

- 1) Range and speed vary with user weight, terrain type, battery charge, battery condition and tyre pressure. This specification can be subject to a variance of (+ 10% or 5%).
- 2) Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 3) Battery weight may vary based on manufacturer.
- 4) Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4, standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities. This specification can be subject to a variance of +10%, -5%.
- 5) AGM or gel-cell type required
- Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

## **FEATURES**

- In-line, front-wheel drive technology
- 40 amp, PG GC 3 controller
- Easy access to batteries from rear
- Simple main frame design for easy serviceability
- Comfort high-back seat with headrest

## **OPTIONS**

- High-back seat with solid seat pan
- Cup holder
- Weather cover
- Rear basket
- Oxygen tank holder
- Cane/crutch holder
- Walker holder

## **COLOURS**





Jazzy Red

Jazzy Blue



20-24 Apollo Drive, Hallam, Victoria 3803

ACN 088 609 661 ABN 66 088 609 6611

(Tel) 03 8770 9600 • (Fax) 03 9703 2720 • www.pridemobility.com.au

