

# VANGUARD

## 4-wheel scooter



Full front and rear lighting package



### Cutting Edge Styling, Great Performance

The Peak-Care Vanguard 4-wheel scooter brings a new level of performance features and luxury to personal mobility. Featuring speed reduction technology, which automatically reduces travel speed while turning corners, the Peak-Care Vanguard scooter is a stylish, state-of-the-art package.



Vanguard 4-wheel shown in Blue

# VANGUARD


## 4-wheel scooter

### SPECIFICATIONS

Available Colors	Red / Blue
Overall Length <sup>2</sup>	137 cm (53.93")
Overall Width <sup>2</sup>	67 cm (26.37")
Total Weight	Including Battery Packs 50 Ah : 102.5 kg (225.5 lbs.)
Turning Radius <sup>2</sup>	139.5 cm (54.92")
Speed (maximum) <sup>1</sup>	10 km/h (6.25 mph)
Range Per Charge <sup>1,4</sup>	Up to 33 km (20.62 miles)
Ground Clearance <sup>2</sup>	6 cm (2.36")
Weight Capacity	160 kg (350 lbs.)
Standard Seating Type <sup>5</sup>	Reclining seat with headrest
Drive System	Rear-wheel drive, sealed transaxle, with 24 volt, DC motor
Dual Braking System	Electronic, regenerative, and electromechanical
Tyres	Pneumatic Front and rear: 27.94 cm (11")
Battery Requirements Type <sup>3,6</sup> :	(2) 12-volt, deep cycle, 50 Ah Weight: 13 kg (28.6 lbs.) each
Battery Charger	5-amp Off-board charger
Maximum Safe Slope	14.1% (8°)

### FEATURES

- Speed reduction technology, automatically reduces speed when turning corners
- Independent front suspension, mono shock rear suspension
- Luxurious leg room
- High visibility, front and rear lighting package
- Easy-drive tiller with wraparound handles
- Sleek, modern styling
- Available in your choice of Blue or Red models



<sup>1</sup> Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. This specification can be subject to a variance of (+ or -) 10% - 5%.

<sup>2</sup> Due to manufacturing tolerances and continued product improvement, this specification is subject to a variance of +/- 3%.

<sup>3</sup> AGM or gel cell type required.

<sup>4</sup> Tested in accordance with ANSI/RENSA, WC Vol 2, Section 4, and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

<sup>5</sup> Includes standard seat.

<sup>6</sup> Battery weight may vary based on manufacturer.

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

