



Redefining Patient Handling



Stature



Joerns Oxford® Stature

The Oxford® Stature is a vertical patient lift, recognising the true needs of the modern care environment. With an extensive lifting range, the Stature copes easily with even the most demanding of patient handling situations. Careful attention to product design ensures correct ergonomic usage, protecting both the patient and caregiver from injury.

Key Features

- Safe Working Load 227kg / 35st / 500lbs
- Outstanding lifting range (390mm - 1550mm)
- Ergonomic design considerations
- Powered leg positioning
- Interchangeable spreader bar/cradle configurations
- Stretcher and digital weigh-scale options



Outstanding lifting range

The Stature's incredible lifting range ensures it can cope easily with the most critical of transfers, particularly in acute/institutional environments where variable height beds and special lift mattresses may be encountered. Examples include:

- Chair to chair transfers
- Bed to chair transfers
- Floor to chair transfers
- Chair to bath transfers

Securi3 Sling Clip System

The 4-point positioning cradle (standard option) enables the carer to re-position the patient simply by rotating the cradle (and patient) into a fully seated or reclined orientation.

In combination with Oxford's unique 'Securi3' sling attachment system you can be assured that patient safety is not compromised. The Securi3 system ensures that no inadvertent detachment occurs, once the sling clip has been attached to the cradle. This guarantees that each transfer is achieved safely and efficiently, each and every time.



Ergonomic design considerations

5 The Stature was designed with the five key principles of moving and handling in mind. This direct correlation ensures Oxford's lift designs are simple, safe and above all comfortable to use.

This view is shared by our clinical consultant team, who have assisted us in conducting detailed usability surveys to ensure the Stature meets the true needs of the patient, carer and the environment in which it operates.

- 1 Get close to the load
- 2 Use a wide stable base
- 3 Ensure a comfortable firm grasp
- 4 Keep spine close to neutral
- 5 Make sure movement is smooth



Foot 'push pad' helps reduce the force needed to initiate forward movement.



Over-sized push handle for improved handling and manoeuvrability.



Hand control clip ensures convenient storage when not in use.



Powered leg positioning

The Stature incorporates two powerful electric motors which open and close the legs automatically via the hand control. In addition, the unique 'swan-neck' leg design allows the lift to get close to obstacles such as large chairs, bulky commodes and wheelchairs.



Interchangeable spreader bar/cradle and weigh-scale options

One of the restrictions of using certain lifts is the type of slings you can use. The Stature however, with its interchangeable spreader bar and cradle options, gives you a choice of sling systems.

The Stature can also be fitted with an optional digital weigh-scale device to aid patient monitoring. This Class III certified weigh-scale is extremely compact and has a dual screen display for ease of use.



6-point spreader bar



Manual or powered 4-point cradles



6-point adjustment cradle for use with a stretcher



Digital weigh-scale (Class III)

Technical Specifications

Specification	Imperial	Metric
Safe Working Load	500 lbs	227 kgs
Maximum Overall Length	54.7 inches	1390 mm
Minimum Overall Length	50.8 inches	1290 mm
Maximum Overall Height	83.8 inches	2130 mm
Minimum Overall Height	76.6 inches	1945 mm
Maximum Height to Attachment Point - 4-point Cradle	61.0 inches	1550 mm
Minimum Height to Attachment Point - 4-point Cradle	15.4 inches	390 mm
Maximum Height to Attachment Point - 6-point Spreader Bar	77.7 inches	1975 mm
Minimum Height to Attachment Point - 6-point Spreader Bar	26.6 inches	675 mm
Turning Radius	61.0 inches	1550 mm
Legs Open - External Width	53.5 inches	1360 mm
Legs Open - Internal Width	48.4 inches	1230 mm
Legs Closed - External Width	29.9 inches	760 mm
Legs Closed - Internal Width	25.1 inches	640 mm
Overall Height of Legs	4.3 inches	110 mm
Ground Clearance	1.2 inches	30 mm
Front Twin Castors	4.0 inches	100 mm
Rear Braked Castors	4.0 inches	100 mm

Weights	Imperial	Metric
Mast, Base & Boom Assembly	142 lbs	64.5 kgs
4-point Positioning Cradle (manual operation)	13.2 lbs	6.0 kgs
Power Pack	6.6 lbs	3.0 kgs
Total	162 lbs	73.5 kgs
4-point Positioning Cradle (powered operation)	19.8 lbs	9.0 kgs

Specifications may vary due to manufacturing tolerances

Electrical Specifications (Lift)

Battery 1 x 24 volt rechargeable sealed lead acid type
 Battery capacity 2.9 Ampere hours
 Charger rated input 100 - 240 V AC / 50 / 60 Hz
 Charger rated output 29.5 V DC Max 19W / IPX5

Electrical Shock Protection

Charger - class II
 Lift - internal power source



Degree of shock protection

Charger - Type B
 Lift - Type B

Intended operating environment

>+5° <+40°
 Outside this environment functionality and safety may be compromised

Warranty

Please contact your authorised distributor for details.

