

# Luxury, Performance and Style



**CELEBRITY XL  
DELUXE**

4-Wheel Scooter



Angle-adjustable tiller


The **Celebrity® XL Deluxe** Scooter combines an aggressive outdoor design with luxury features. This feature-rich scooter takes the Celebrity line to an even higher level of refinement in scooter design with our new independent console angle adjustment, deluxe high-back reclining captain's seat, full directional light package and one-handed tiller angle adjustment, making it the best outdoor scooter in its class.

PRIDE® **MOBILITY SCOOTERS**  
LIVE YOUR BEST®

| [pridemobility.com.au](http://pridemobility.com.au) |



# Specifications 4W: SC4450DXAUS

Weight Capacity	159 kg (350 lbs.)
Maximum Speed <sup>1</sup>	Variable up to 12 km/h (7.5 mph)
Ground Clearance <sup>2</sup>	10.79 cm (4.25")
Turning Radius <sup>2</sup>	168.27 cm (66.25")
Overall Length <sup>2</sup>	130.17 cm (51.25")
Overall Width <sup>2</sup>	64.13 cm (25.25")
Front Tyres	10 cm x 33 cm (4" x 13") Pneumatic
Rear Tyres	10 cm x 33 cm (4" x 13") Pneumatic
Range Per Charge <sup>2,4</sup>	Up to 40.23 km (25 miles)
Total Weight Without Batteries	90.71 kg (200 lbs.)
Heaviest Piece When Disassembled	37.64 kg (83 lbs.) front section
Standard Seating	Type: CRS Deluxe Material: Black Vinyl Dimensions: Width: 46 cm (18"), Depth: 46 cm (18")
Motor Output	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Brakes	Regenerative and electromechanical
Battery Requirements <sup>3,5</sup>	(2) 12-volt, deep cycle Size: (2) 40 AH Weight: 14.7 kg (32.5 lbs.) each
Battery Charger	5-amp, off-board
Colour	

Red

**NOTE: All specifications subject to change without notice.**

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.

## Features

- Front frame mounted seat post for optimal stability
- Restyled lightweight front basket included
- Easily accessible securement points (for transport of an unoccupied scooter)
- High visibility reflectors
- Microprocessor-based controller for optimal power management
- Ultra-simple, auto-latching frame lockup for quick disassembly and assembly
- Standard angle-adjustable dual bulb lower headlight for optimal pathway illumination
- Independent angle-adjustable console
- One-handed operational squeeze lever and auto-locking mechanism for convenient tiller angle adjustment
- Full directional lighting package including front and rear turn signal indicators
- Two rearview mirrors standard

## Options

- Accepts both 40 AH and 50 AH batteries for optimum charge

## Accessories

- Pride® rear bag (includes crutch/walking stick holder)
- Walker holder (must have Pride® rear bag to attach)
- Oxygen tank holder (must have Pride® rear bag to attach)
- Saddlebag
- Mobile phone holder
- Cup holder
- Flag
- Rearview mirror

<sup>1</sup> Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).

<sup>2</sup> Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

<sup>3</sup> AGM or gel cell type required.

<sup>4</sup> Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

<sup>5</sup> Battery weight may vary based on manufacturer.