



Feather-Touch Disassembly

The **Go-Go Elite Traveller** Plus offers style and performance for your on-the-go lifestyle. Standard features include a delta tiller with wraparound handles, feather-touch disassembly, black, non-scuffing tyres, a front basket and an 17 AH battery pack. A 136 kg (299 lbs.) weight capacity and a maximum speed up to 7.25 km/h (4.5 mph) complement the versatility of the Go-Go Elite Traveller® Plus.











Specifications 4W: SC54

Weight Capacity	136 kg (299 lbs.)
Maximum Speed ¹	Up to 7.25 km/h (4.5 mph)
Ground Clearance ²	3.8 cm (1.5") at motor
Turning Radius ²	116.2 cm (45.75")
Overall Length ²	102.24 cm (40.25")
Overall Width ²	54 cm (21.25")
Front Tyres	5.1 x 18 cm (2" x 7") solid
Rear Tyres	6.3 x 20 cm (2.5" x 8") solid
Range Per Charge ^{1,4}	Up to 21 km (13 miles)
Total Weight Without Batteries	35.6 kg (78.5 lbs.)
Heaviest Piece When Disassembled	15.88 kg (35 lbs.) <i>(front section)</i>
Standard Seating	<i>Type:</i> Foldable, compact, vinyl-covered, molded plastic
Motor Output	24-volt DC motor, sealed transaxle
Brakes	Regenerative and electromechanical
Battery Requirements ^{3,5}	Size: (2) 17 AH Weight: 6.4 kg (14 lbs.) each 13.2 kg (29 lbs.) per battery pack
Battery Charger	Off-board, 2 amp
Colours	2 sets with every scooter!

Features

- Convenient dual voltage charger can charge battery pack on-board or off-board
- Delta tiller with wraparound handles Feather-
- touch disassembly permits simple frame separation with only one hand and easily disassembles into five super lightweight pieces for convenient transport and storage
- Front frame-mounted seat post offers maximum stability
- Front tiller-mounted basket
- Includes two sets of easily changeable, red and blue coloured panels
- Microprocessor-based controller offers optimal power management and added safety features
- Pride's exclusive black, non-scuffing tyres
- Removable footboard basket for additional storage (4-wheel version only)

Accessories

- Pride® rear bag (includes crutch/walking stick holder)
- Walker holder (must have Pride® rear bag to attach)
- Oxygen tank holder (must have Pride® rear bag to attach)
- Saddlebag
- Mobile phone holder
- Cup holder
- Flag
- Rearview mirror

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- 3 AGM or gel cell type required.
- 4 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5 Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.











Red



Blue



