## The Smoothest Ride in Travel Mobility



Comfort-Trac Suspension

The Go-Go® LX with Comfort-Trac Suspension (CTS) offers a whole new level of comfort and performance. This industry-first CTS technology incorporates advanced suspension for improved absorption over various terrains. The Go-Go LX with CTS offers a 136 kg (300 lb.) weight capacity, a per charge range up to 16.9 km (10.5 miles) and a maximum speed of 6.4 km/h (4 mph). Standard features include feather-touch disassembly, a wraparound delta tiller (with charger port), non-scuffing tyres, LED headlight and front basket.

## Go-Go LX (CTS Suspension) Specifications

| Weight Capacity                                | 136 kgs (300 lbs.)  |
|--|---|
| Maximum Speed <sup>1</sup>                     | Up to 6.4 km/h (4 mph)  |
| Ground Clearance <sup>2</sup>                  | 3.8 cm (1.5") at motor  |
| Turning Radius <sup>2</sup>                    | 116.2 cm (44.75")   |
| Overall Length <sup>2</sup>                    | 104.1 cm (41")  |
| Overall Width <sup>2</sup>                     | 52.1 cm (20.5")   |
| Front Tyres                                    | 5 x 17.8 cm (2" x 7") solid   |
| Rear Tyres                                     | 6.35 x 20.3 cm (2.5" x 9") solid  |
| Range Per Charge <sup>1,4</sup>                | Up to 16.9 km (10.5 miles)  |
| Total Weight<br>Without Batteries <sup>5</sup> | 39.6 kg (87.4 lbs.)   |
| Heaviest Piece When<br>Disassembled            | 16.6 kg (36.6 lbs.) (front section)   |
| Standard Seating                               | Type: Foldable, vinyl covered, molded plastic Weight: 10 kg (23 lbs.) Material: Black vinyl Dimensions: Width: 43.1 cm (17") Depth: 43.1 cm (17") |
| Motor Output                                   | 24-volt DC motor, sealed mini-transaxle   |
| Brakes   | Regenerative and electromechanical  |
| Battery Requirements <sup>3,5</sup>            | (2) 12V deep-cycle<br>Size: (2) 17 AH<br><b>Weight</b> : 13.8 kg (30.4 lbs.) per<br>battery pack  |
| Battery Charger                                | Off-board, 2 amp  |
| Delta Tiller                                   | Yes   |
| Colour Options                                 |   |
|  |   |

## **Features**

- Charger port built into the tiller
- Convenient dual voltage charger that can charge battery pack on-board or off-board
- Comfort-Trac front and rear suspension
- Feather-touch disassembly
- Front frame-mounted seat post offers maximum stability
- Long-lasting, high-intensity, front LED headlight
- Microprocessor-based controller
- Pride's exclusive black, non-scuffing tyres

## Accessories

- Pride rear bag/walking stick holder
- Walker holder\*
- Oxygen tank holder\*
- Mobile phone holder
- · Cup holder
- · Rear view mirror
- Saddle bag
- Flag

\*Must have Pride rear bag to attach

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or 3%).
- 3 AGM or gel cell type required.
- 4 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5 Battery weight may vary based on manufacturer

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or – 3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.









(Tel) 03 8770 9600 • (Fax) 03 9703 2720 www.pridemobility.com.au

