# Comfort, Performance and Added Style



Feather-touch disassembly

The sleek and sporty **Pathrider® 10** offers added style, comfort and performance for your active lifestyle. Standard features include an LED lighting package, back-lit battery gauge, feather touch disassembly, wraparound easy-drive tiller, 25 cm (10") solid tyres and front basket. A 159 kg (350 lbs.) weight capacity, a per charge range of up to 25 km (15.5 miles) and a maximum speed up to 8.5 km/h (5 mph) compliment this versatile scooter.

PATHRIDER

4-Wheel Scooter

PRIDE<sup>®</sup> MOBILITY SCOOTERS LIVE YOUR BEST<sup>®</sup>

Visit pridemobility.com.au to learn more

## Pathrider 10 **Specifications**

| Weight Capacity                     | 159 kgs (350 lbs.)                                                                                                                                                                        |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Maximum Speed <sup>1</sup>          | Up to 8.5 km/h (5 mph)                                                                                                                                                                    |
| Ground Clearance <sup>2</sup>       | 5 cm (2")                                                                                                                                                                                 |
| Turning Radius <sup>2</sup>         | 157.5 cm (62")                                                                                                                                                                            |
| Overall Length <sup>2</sup>         | 119 cm (47")                                                                                                                                                                              |
| Overall Width <sup>2</sup>          | 56.5 cm (22.25")                                                                                                                                                                          |
| Front Tyres                         | 25 cm (10") solid                                                                                                                                                                         |
| Rear Tyres                          | 25 cm (10") solid                                                                                                                                                                         |
| Range Per Charge <sup>2,4</sup>     | Up to 25 km (15.5 miles)                                                                                                                                                                  |
| Total Weight<br>Without Batteries   | 63.5 kg (140 lbs.)                                                                                                                                                                        |
| Heaviest Piece<br>When Disassembled | 32 kg (71 lbs.) (front section)                                                                                                                                                           |
| Standard Seating                    | <b>Type</b> : Foldable, vinyl-covered, molded plastic<br><b>Weight</b> : 13 kg (28 lbs.)<br><b>Material</b> : Black vinyl<br><b>Dimensions</b> : Width: 46 cm (18")<br>Depth: 43 cm (17") |
| Motor Output                        | 24-volt DC motor, sealed mini-transaxle                                                                                                                                                   |
| Brakes                              | Electronic, regenerative<br>and electromechanical                                                                                                                                         |
| Battery Requirements <sup>3,5</sup> | (2) 12V deep-cycle<br><b>Size</b> : 35 AH (standard) or 40 AH (optional)<br><b>Weight</b> : 35 AH: 15 kg (32.5 lbs.) each<br>40 AH: 15 kg (32.5 lbs.) each                                |
| Battery Charger                     | Off-board, 3 amp                                                                                                                                                                          |
| Colour Options                      |                                                                                                                                                                                           |
|                                     |                                                                                                                                                                                           |

A DESCRIPTION OF A DESC **PRIDE® MOBILITY SCOOTERS** LIVE YOUR BEST®

20-24 Apollo Drive Hallam, Victoria 3803 ACN 088 609 661 ABN 66 088 609 661 (Tel) 03 8770 9600 • (Fax) 03 9703 2720 www.pridemobility.com.au



#### **Features**

- Exclusive one-hand feather touch disassembly provides the ultimate quick transport system
- Easy-drive tiller with wraparound handles
- Back-lit battery gauge •
- Exclusive stylish, lightweight, non-scuffing, black, low-• profile tyres
- Long-lasting, high-intensity LED headlight offers optimal pathway illumination
- Lightweight pinchless hinge seat, eight position rotation, sliders and viscoelastic foam inserts for increased comfort
- Easy-grip tiller adjustment knob ٠
- · Easy-access tiller-mounted charger port
- Auto-connecting front-to-rear harness

### Accessories

- Pride rear bag/walking stick holder
- Walker holder\*
- Oxygen tank holder\*
- Mobile Phone holder
- Cup holder
- Saddle bag
- Flag

#### \*Must have Pride rear bag to attach

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).
- Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or 3%).
- AGM or gel cell type required. Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 4 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.5 Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or -3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.